

Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

×

Date: 04/18/2024 - 11:42 PM *

EXF #: BF-010596

Category: BORING - FEED THROUGH

Brand / Model: MORBIDELLI "CN 3A / CN 3B"

Machine Type: BORING MACH. (FEED THRU CNC

W/DOWELING)

Year of Mfg. :

Condition: Reconditioned

Elect / Voltage: 400/440 V, 50/60 Cy, 3 Ph.

Special Note: Make Offer

FOB / Region: EUROPE

Appr. Repl. Cost.: € 360,000

Price : €0 *

Comment: Seller States, "This line was

RECONDITIONED and PA

Leasing: Contact NCL for quote

Please ask me



800-374-5009 ext. 346 Intl. +1 704-841-2001 ext. 346 bob.bullin@exfactory.com

* Pricing is valid at the time of printing and subject to change at any time.

Description:

MORBIDELLI CN 3A / CN 3B BORING MACH. (FEED THRU CNC W/DOWELING):

POS #1: MORBIDELLI CN 3A CNC Feed Through Boring Machine

- 3,200 mm (126") Max. opening cap. in "X" axis left-right; 215 mm (8-1/2") min. opening cap.; 1,056 mm (41-1/2") max. "Y" axis front-back cap.; 100 mm (3.9") min. front-back capacity.
- Right & Left horizontal boring units: Each with: (1) 20-spindle chucks on 32 mm centers; each chuck powered by 1.8 HP (1.3 kW) motor; right horizontal unit motorized & left horizontal unit is fixed.
- (4) CNC Controlled double top clamp hold-down cylinders.
- (6) CNC Controlled BOTTOM vertical supports.
- (2) CNC Controlled TOP vertical supports.



Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

 Each vertical can be equipped with: (2) Boring blocks (swivel 0° - 90°); each boring block driven by 2.3 HP (1.7 kW) motor.

All **VERTICAL** supports equipped with: Pneumatic locking, individual adjustment for boring block distance, readouts on all heads for finite adjustments, boring depth controlled by a programmable "Z" axis Servo drive.

- The programmable Servo drive: Allows for tight control of the boring depth, as well as the feed belt speed control which is variable from 35 75 MPM (114 246 FPM).
- 670 mm (26") Long outfeed belt transfers with up/down flip movement for ease of machine adjustments; removable panel support rails; safety light curtains.
- POS #2: MORBIDELLI CN 3B, ...CNC Feed Through Boring Machine with Dowel Inserting: 3,200 mm (126") Max. opening cap. in X-axis left-right; 215 mm (8-1/2") min. opening cap.; 1,056 mm (41-1/2") max. Y-axis front-back cap.; 100 mm (3.9") min. front-back capacity.
- Right & Left horizontal doweling units with: (5) glue & dowel inserting units on each side; right horizontal
 unit motorized & left horizontal unit is fixed.
 - (2) Vibrator Hoppers with: (5) Horizontal dowel tubes on each hopper that allows up to (5) dowels to be inserted at the same time on each side.

Equipped with: Automatic dowel measurement device, pressurized glue tank, & rinsing tank.

- (2) CNC Controlled double top-clamp holddown cylinders.
- (3) CNC Controlled BOTTOM vertical supports.
- Each vertical can be equipped with: (2) Boring blocks (swivel 0° 90°); each boring block driven by 2.3 HP (1.7 kW) motor.

All **VERTICAL** supports are equipped with: Pneumatic locking; individual adjustment for boring block distance; position readouts on all heads for finite adjustments; and boring depth controlled by a programmable "Z" axis Servo drive.

- The programmable Servo drives allows: Tight control of the boring depth, as well as the feed belt speed control, which is variable from 35 75 MPM (114 246 FPM).
- 670 mm (26") Long infeed double belt transfers with up/down flip movement for ease of machine



Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

adjustments; removable panel support rails; safety light curtains.

- The numerical control allows for CNC setup of "X", "Y1" & "Y2" axes of the vertical units, the transport belts & the top clamps in "X" axis.
- The storage of the data within the panel program & the serial transmission of data is transferred to the units on the machine for axes repositioning and to setup the automatic working cycles.
- Options Include: (8) 15-Spindle boring chucks on 32 mm centers; (14) 9-spindle boring chucks on 32 mm centers.

Actual model is: MORBIDELLI - CN 3A / CN 3B.

Note: EX-FACTORY's Logistic Department is experienced and set up to provide "Full Service Logistics" from Overseas Suppliers to your Door. ...Packaging, Container Loading, Ocean Freight, Marine Insurance (door to door), US or Canadian Customs, Duty, and domestic shipping to your Plant Door."