

Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries



Date: 06/03/2025 - 10:18 AM *

EXF #: BP-012772

Category: CNC POD & RAIL MACH. CTR.

Brand / Model: HOMAG "BOF 612"

Machine Type: CNC MACHINING CENTER (2-HEAD)

Year of Mfg.: 2008/

Condition: Fair Condition

Elect / Voltage: 600 V, 60 Cy, 3 Ph.

Special Note: In Auction

FOB / Region: MEXICO

Appr. Repl. Cost.: \$ 690,000

Price: \$ 42,500 *

Comment: Priced to sell quickly!

Leasing: Lease for \$ 864/Mo. at NCL

×

Please ask me

James Sullivan

800-374-5009 ext. 378

Intl. +1 704-841-2001 ext. 378

james@exfactory.com

Description:

- HOMAG BOF 612: CNC "Gantry" 2-HEAD Machining Center
- **HOMAG "BOF 612"** (Weight 7,000 kG/15,400 Lbs): The working unit is mounted on a Heavy-Duty overhead "GANTRY" System for all "X" & "Z" axis movements & functions; "Y" axis movement is performed by twin shuttle tables that work in tandem or independently of each other.
- "BOF 612" Working Field for single panel processing with: "X" Axis: 3,470 mm (136.6"); "Y" axis: 1,300 mm (51"); "Z" axis: Stroke 600 mm (23.6"); max. material thickness 300 mm (11.8").
 When processing (2) panels at a time: "X" Axis 1,700 mm (66.9") x 2; "Y" axis 1,300 mm (51").
 When processing (4) panels at a time: "X" Axis 700 mm (27-1/2") x 4; "Y" axis 500 mm (19.7") x 2.
- "BOF 612" Positioning Speed: "X" & "Y" Axis: 60 MPM (197 FPM); "Z" axis: 30 MPM (98 FPM); AC Brushless Servo motors with: Digital drive & linear guides ensure high speeds with a smooth acceleration & deceleration.

 $^{^{\}star}$ Pricing is valid at the time of printing and subject to change at any time.



Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

- "BOF 612" Working Tables: Tables consist of (8) adjustable "K-table" support rails (4 rails with 4 pneumatic lifters in each zone); (3) vacuum pods per rail; manual positioning of rails & vacuum pods via LED positioning indicators according to the parts processing requirements from the NC control.
- "BOF 612" Machining Units: (2) 20 HP (15 kW) Liquid-cooled electrospindle Router with: "HSK F63" Adaptor; (2) NC controlled "FLEX5" "C" axis for 360° horizontal processing at angles from 0° 90° (1,000 20,000 RPM); (2) 10-position "on the fly" tool changers.
- "BOF 612" Boring Units: (2) 1.5 kW (2 HP) Motors; variable speed from 0 7,500 RPM; (2) 9-spindle vertical unit with 4-spindles in "X" axis & 5-spindles in "Y" axis; (4) horizontal spindles with (1 + 1) in "X" axis & (1 + 1) in "Y" axis.
- IPC Front- End with: HOMAG "Power Control PC 85" + Windows "XP" + "WOODWOP 5.0 + "FLEX5" + BOF GANTRY" Operating System; icon driven software with graphic interface to allow the Ooperator to quickly and efficiently create programs.
- Control includes: 1.44 MB Disk drive; CD/RW drive; 17" TFT flat screen monitor; Ethernet network connection; RS-422 serial & USB connection to PC (up to 300 meters); (2) line adaptors RS-232 & 485.2 with 9-25 pin and card for RS-232 line (cable not included).
- **Control Features**: Multitask Operating System; input/output modules; axes override; 4-axis interpolation; diagnostic graphics aid for programming; machine data & tool management.
- Editor Module for office PC with same look and functionality of software on the machine; allows transmission of programs and work lists.
- Line System complete with: (2) Liquid Rings, 340 cbm/Hr (15 HP) vacuum pumps; LH & RH scrap sliders & LH direction scrap removal belt conveyor.
- Handheld pendant; perimeter protection cages; user & maintenance manuals on CD with wiring diagrams and operation of Numerical Control; system complies with EU/CSA/UL safety standards.

Actual model: HOMAG "Optimat BOF 612/34/13/2K"