

Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries



Date : 07/01/2025 - 1:20 AM *

EXF #: EO-012587

Category: EDGEBANDERS-OVER \$25,000

Brand / Model: CEHISA "PRO-12"

Machine Type: EDGEBANDER (W/PRE-MILL &

CORNER ROUNDING)

Year of Mfg.: 2018

Condition: Cleaned and checked

Elect / Voltage: 600 V, 60 Cy, 3 Ph.

Special Note:

FOB / Region: EASTERN CDN

Appr. Repl. Cost.: \$ 79,500

Price: \$51,600 *

Comment: Ready to operate for you

Leasing: Lease for \$ 1,037/Mo. at

NCL



Please ask me

800-374-5009 ext. 346 Intl. +1 704-841-2001 ext. 346 bob.bullin@exfactory.com

* Pricing is valid at the time of printing and subject to change at any time.

Description:

- CEHISA PRO-12 EDGEBANDER (W/PRE-MILL & CORNER ROUNDING):
- Features:

Pre-Milling Station with:

2 x 1.5 Kw (2.0 HP) 12,000 RPM motors, standard equipped with diamond cutters. Both spindles pneumatically controlled.

- Spray agent unit for top and bottom with (2) sprayer and (2) reservoir
- Automatic Edge Magazine:

For coiled material up to 3 mm thickness, strip feed magazine for up to 5 mm (3/16") solid wood banding.

Quick Melt Glue System, MR-5:

10 - 15 min. heat-up time, auto temperature drop. Glue Tank is coated with nonstick material, quick-change mechanism for easy maintenance and/or color change.



Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

Pressure Section:

(1) Large dia. driven and (2) idle rollers. Digital read-out and pneumatic positioning selectable from controller touch screen.

Edgebanding Workstations:

- End Trimming Station, V-7: Double motor front & rear, 2 x 0.35 Kw (0.5 HP) 12,000 RPM.
- **Edge Trimming Station, BC-5:** Top & bottom flush/bevel/radius trimming, 2 x 0.55 Kw (0.75 HP) 12,000 RPM, tiltable 0° 10°, pneumatic exclusion from operator panel.
- Corner Rounding Unit, FD-50: To process overhanging edges and trimming around the leading & trailing edge, 1 x 0.27 Kw (0.36 HP).
- **Profile Scraping Unit, R-8:** For thick PVC/ABS radius scraping, pneumatic in/out positioning from control panel with chip collection box.
- Flat Glue Scraper, RR-7: To remove potential glue squeeze-out.
- **Buffing Unit, PC-9**: with spry mist unit top/bottom Top/Bottom, 2 x 0.12 Kw (1/8 HP) 1,650 RPM motors, tilting horizontally and vertically.

Operator Interface:

PLC Microprocessor control with color touch screen, memory up to 20 programs.

Equipped With:

Feed Speed, 9 - 14 MPM (29' to 45 FPM),

Power hold-down beam, work-piece support outrigger, safety & sound enclosure.

Included Options:

Riepe, non-stick spray system.

Nesting Tracer Shoes for top/bottom trimmers