



**Date :** 05/21/2026 - 12:32 PM \*

**EXF # :** EO-012672

**Category :** EDGEBANDERS-OVER \$25,000

**Brand / Model :** SCM "OLIMPIC K360"

**Machine Type :** EDGEBANDER (W/PRE-MILL & CORNER ROUNDING)

**Year of Mfg. :** 2023

**Condition :** Like New

**Elect / Voltage :** 230 V, 60 Cy, 3 Ph.

**Special Note :**


**FOB / Region :** PACIFIC NORTHWEST

**Appr. Repl. Cost. :** \$ 90,000

**Price :** **\$ 67,000 \***

**Comment :** This Bander is READY to process materials for you!

**Leasing :** Lease for \$ 1,346/Mo. at NCL



Please ask me

**Bob Bullin**  
 800-374-5009 ext. 346  
 Intl. +1 704-841-2001 ext. 346  
 bob.bullin@exfactory.com

\* Pricing is valid at the time of printing and subject to change at any time.

**Description :**

- **SCM OLIMPIC K360 ERT HP: Compact Edgebander (w/Premill & Corner Rounding)**

**Specifications**

- Edge Capacity: 0.4 - 6 mm (0.016 to 1/4") For strip feeding.
- Panel Capacity: Min. width 65 mm & 140 mm min. length (2-3/8" & 5-1/2"); panel thickness: Min./max. 8 - 60 mm (3/8" - 2-1/2").

**Equipped with:**

- Adjustable Infeed Fence: Manually preset with digital indicator, pneumatic in/out positioning.
- Premilling Station RT-VP: Spindles (2) x 2.0 HP - 19,000 RPM; (1) with PLC controlled jump action & diamond cutterheads.

**Sales - Liquidations - Auctions - Appraisals - Consulting**



Machinery for the Woodworking, Stone,  
Glass, Plastic, and Metalworking Industries

---

- Automatic Strip & Coil Feed Magazine: For straight edges & 3 mm guillotine for coils.
- Gluing Station for EVA (Hot Melt) with: Teflon coated glue tank & quick disconnect to change glue tanks fast if needed; heat up time: Approx. (10) Min.
- Pressure Section: Manual digital positioning; (3) pressure rollers: First larger; Teflon coated & powered.

#### **Workstations**

- End Trimming Station. Front & rear: (2) x 1/4 HP - 12,000 RPM motors; mounted on THK guides; swivels 0° - 15°; rapid setup between straight & angled cutting with: Automatic swivel cylinder.
- Trimming Unit Flush/Bevel/Radius: Top/Bottom remote (via control panel) pneumatic positioning for (3) settings; Flush/bevel/radius trimming; (2) x 0.7 HP - 12,000 RPM motors with: Precision digital indicators for quick setup.
- Corner Rounding Unit "Round 2M" with: (2) 0.8 HP Independent motors that slide on THK guides.
- Profile Scraping Unit "RAS/V": Top/Bottom, manual preset up with digital indicators; large dia. copy wheels for max. accuracy & pneumatic in/out positioning.
- Buffing Unit: Top/bottom; (2) x 1/4 HP - 2,800 RPM motors; tilting up to 12°.

#### **Operator Interface**

- ORION "1 Plus" Controller. Fixed at infeed of machine with: "Touch Screen" control with soft keys, graphics, & LCD display panel; handles most machine setup functions & workstations.

#### **Complete with & Features**

- Feed speed: 36 FPM Fixed; (1) x 2.0 HP feed drive motor; 200 Hz frequency inverter for all trimming units.
- Manual adjustable hold-down pressure beam; full sound enclosure cover; outboard panel support.
- Actual Model: **SCM OLIMPIC K360 ERT HP**

---

**Sales - Liquidations - Auctions - Appraisals - Consulting**

**EX-FACTORY INC.:** 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068  
**Warehouse & Showroom:** 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328



**Machinery for the Woodworking, Stone,  
Glass, Plastic, and Metalworking Industries**

---

**Sales - Liquidations - Auctions - Appraisals - Consulting**

---

**EX-FACTORY INC.:** 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068  
**Warehouse & Showroom:** 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328