



**Machinery for the Woodworking, Stone,  
Glass, Plastic, and Metalworking Industries**



**Date :** 04/16/2024 - 12:41 PM \*  
**EXF # :** FD-010845  
**Category :** FINISHING-SAND/DENIBBERS  
**Brand / Model :** OPTI-SAND "L202"  
**Machine Type :** SEALER/DENIBBER SANDER  
**Year of Mfg. :**  
**Condition :** Very good condition  
**Elect / Voltage :** 230 V, 60 Cy, 3 Ph.  
**Special Note :** Great Value

**FOB / Region :** MIDWEST  
**Appr. Repl. Cost. :** \$ 25,000  
**Price :** **\$ 10,800 \***  
**Comment :** "Excellent" Condition machine at an "Excellent" pr  
**Leasing :** Lease for \$ 219/Mo. at NCL



Please ask me

**Dan Wolters**  
800-374-5009 ext. 376  
Intl. +1 704-841-2001 ext. 376  
dan.wolters@exfactory.com

\* Pricing is valid at the time of printing and subject to change at any time.

### **Description :**

- **OPTI-SAND L202 Abrasive Brush Feed Through Sander;**

2-Head Abrasive Brush Sander with (1) top & (1) side heads use standard abrasive heads or cored brush loadings (not included). **11-3/4" Width and 4" height capacity.**

#### **Specifications:**

- Overhead counter-rotating arbor, 12" long arbors x 12" max. dia. sanding discs.
- Head is mounted on a height adjustable common plate with a slide assembly.
- Head tilts up to 15° and 1 HP Motor drives each arbor with inverter for variable 100 - 1,000 RPM arbor rotation speed.
- (1) Side mounted abrasive/brush head, tilt and front head adjusts in-and-out via locking hand-wheel, 6" long arbors x 8" dia. max. sanding discs.

**Sales - Liquidations - Auctions - Appraisals - Consulting**

**EX-FACTORY INC.:** 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068  
**Warehouse & Showroom:** 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328



**Machinery for the Woodworking, Stone,  
Glass, Plastic, and Metalworking Industries**

---

- 0.5 HP Motor drives each arbor with inverter for variable 100 - 1,000 RPM arbor rotation speed; all arbors are 50 mm hexagonal for positive non-slip rotation.

**Feed System:**

- 0" - 5" Max. part height adjustment via locking hand-wheels; 86" long fixed roller conveyor feed bed with rubber rollers,
- (2) 0.25 HP DC motor drives with variable feed speed 10 - 100 FPM
- (6) Full width overhead soft rubber pressure rollers located at infeed, outfeed and between sanding heads, rollers are connected overhead for quick height adjustments.

**Includes & Features:**

- Centralized control panel with digital displays and touch screen controls for spindle speed and feed rate.
- (2) 4" Dia. dust ports, min. 1,400 CFM dust collection required.

---

**Sales - Liquidations - Auctions - Appraisals - Consulting**

**EX-FACTORY INC.:** 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068  
**Warehouse & Showroom:** 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328