

Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries



Date : 05/30/2025 - 7:03 PM *

EXF #: GD-010869

Category: GLUE & DOWEL INSERTERS

Brand / Model: KOCH "SPRINT-PTP-2-L"

Machine Type: CNC BORE, GLUE & DOWEL

INSERTER

Year of Mfg.: 2006

Condition : Good Condition

Elect / Voltage: 600 V, 60 Cy, 3 Ph.

Special Note:

FOB / Region: EASTERN CDN

Appr. Repl. Cost.: \$85,500

Price: \$ 34,200 *

Comment: Ready to operate for you

Leasing: Lease for \$ 695/Mo. at NCL

Bob Bullin 800-374-5009 ext. 346

Please ask me

Intl. +1 704-841-2001 ext. 346 bob.bullin@exfactory.com

Description:

• KOCH SPRINT-PTP-2-L CNC BORE, GLUE & DOWEL INSERTER:

Specifications:

Automatic step-by-step, boring, glue injection & dowel insertion at random spacing.

Working Capacity:

Stock length (Y) from 4.25" - 31.4" (110 mm - 800 mm), Stock width (X) from 0.75" - 98.4" (20 mm - 2,500 mm).

Stock thickness (Z) from 0.51" - 1.57" (13 mm - 40 mm), max. boring depth 1.1" (28 mm). 98.4" (2,500 mm) X-Axis divided into (2) work zones of 47.2" (1,200 mm) ea zone. One part can be processed, while the other is being unloaded or loaded.

Positioning Speed:

344.5 FPM (105 MPM), boring & insertion capacity up to (60) dowels/Min

^{*} Pricing is valid at the time of printing and subject to change at any time.



Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

Machining:

(1) Horizontal boring spindle, 7,200 RPM, powered by 1.2 HP (0.9 kW) motor; (1) Glue injection & dowel inserting system,

Dowel inserter is set up for 8 mm dia. x 30 - 35 mm long dowels (other dimensions available).

Operator & Machine Control:

12." Color touch screen monitor using Windows XP operating system with graphics & diagnostic. serial interface & USB connection.

Menu driven operator interface for function control and graphic illustration of machine functions

Complete with:

Central lubrication system; (1) Vibrating hopper for dowel delivery; (8) Stock clamping cylinders; (1) Removable center stop for up to (2) working zones; "Air tight" pressurized 1:1 glue tank.(was only used with water)

- (2) Fixed fences (RH & LH side), double sided center fence.
- Actual Model is KOCH SPRINT-PTP-2-L