



Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries



Date : 08/07/2025 - 2:31 AM *
EXF # : PL-011703
Category : PLANERS - SINGLE & FACING
Brand / Model : POWERMATIC "WP-2510"
Machine Type : SINGLE SURFACE PLANER
Year of Mfg. :
Condition : Very good condition
Elect / Voltage :
Special Note : Great Value

FOB / Region : SOUTHWEST
Appr. Repl. Cost. : \$ 18,500
Price : \$ 11,500 *
Comment : Great price on a proven performer
Leasing : Lease for \$ 233/Mo. at NCL

Portrait of Ed Webb with contact information: Please ask me, Ed Webb, 800-374-5009 ext. 377, Intl. +1 704-841-2001 ext. 377, Ed.Webb@exfactory.com

* Pricing is valid at the time of printing and subject to change at any time.

Description :

POWERMATIC WP 2510 PLANER

The POWERMATIC "WP 2510" Planer with a 15 HP motor has a solid steel helical cutterhead with four-sided carbide knife inserts that require no adjustments when changing. With a digital readout and simple PC controller, setting up table heights is quick and easy.

- The frame is machined from heavy cast iron and has extra wide side panels that offer rigid bed support and ensure accurate alignment.
The planer's segmented, serrated infeed roll with segmented chip breakers has an independent yield of 1/4". Its automatically adjusting, chain drive gear box powers the 3" dia. infeed rollers, solid pressure bar and dual outfeed rollers for precise feeding of stock.
The 3-speed feed selector gives woodworkers flexibility by changing feed rates quickly and easily.
The "WP 2510" Planer has a large 32-3/16" x 26" precision-ground table which contains two adjustable table rollers for smooth feeding of uneven stock. The planer has a Quick-Set micro-adjustable lever that

Sales - Liquidations - Auctions - Appraisals - Consulting



**Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries**

easily raises and lowers the table rollers from 0 to 0.05". The hood features a built-in 5" diameter dust chute.

- SPECIFICATIONS:
- Max. planing 25", max. planing thickness 9", max. full width depth of Cut 1/8", max. depth of cut 1/4".
- Min. Planing length 10", cutterhead dia. 3-3/8", cutterhead speed 5,000 RPM, cuts per minute 30,000; 15 HP motor.
- Feed Rate 20, 25 and 30 FPM, Outfeed Roller Diameter 3 "; number of Knives: (174) Four-sided inserts.
- Table Size: 32 3/16" x 26"; dust port diameter 5 ", dust collection CFM Required (600) CFM.
- Bed Rollers adjustable from front fom 0" to 0.05"; Readout Scale: inch/ metric; Table Height adjust manual with 1 Turn = 1/32", (2) column for bed support, 2-1/2" column dia.; (1) infeed and (2) outfeed rollers; includes Tool Kit.

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328