



**Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries**



Date : 04/26/2024 - 9:37 PM *
EXF # : RF-010546
Category : PRESSES-RADIO FREQUENCY
Brand / Model : L & L "DA-80H"
Machine Type : RF EDGE GLUER
Year of Mfg. : 1995
Condition : Reconditioned
Elect / Voltage : 230/460 V, 60 Cy, 3 Ph.
Special Note :

FOB / Region : MID ATLANTIC
Appr. Repl. Cost. : \$ 72,000
Price : **\$ 42,400 ***
Comment : Very clean RF Press -
waiting for you!
Leasing : Lease for \$ 862/Mo. at NCL



Please ask me

Louis Sicotte
800-374-5009 ext. 329
Intl. +1 704-841-2001 ext. 329
louis.sicotte@exfactory.com

* Pricing is valid at the time of printing and subject to change at any time.

Description :

- **L & L - DU ALL DA-80 H, ...High Frequency Press**
- For assembly, clamping, and quick curing of edge banding and edge gluing; platen mounted at 30° angle and top lid opens 45°.
- Capacity: 50" x 80" and up to 4-1/2" thick; hydraulic edge and end pressure enables press to accommodate solid stock up to 4-1/2" thick.

Equipped with:

- Built-in 10 kW generator (to be confirmed).
- Self-contained 5 HP hydraulic unit.

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328



**Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries**

- 2" Bore and 4" stroke hydraulic cylinders on 5-1/2" center provide clamping pressure from side and end.
- (9) Cylinders for side and (14) cylinders for end (horiz.) pressure; long stroke cylinders for top holddown to ensure flat parts.
- High/low pressure allows clamping with low pressure for positioning parts with top platen raised, and high pressure when curing cycle begins.
- Pressure is selectable from end only, side only, or both; with localized pressure by removing clamp cylinder foot.
- The hydraulic system pump provides up to 15x more pressure than air and is fully adjustable when great pressure is not needed (120 PSI on line equals 120 PSI on glue line at 1-1/4" thickness).

NOTE: Pictures are from a different machine that has been reconditioned.

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328