



Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries



Date : 05/08/2021 - 12:23 AM *
EXF # : SX-012372
Category : SANDERS-MULTI.HD/POLISHER
Brand / Model : SCM "SANDYA CLK 3 G"
Machine Type : 2-HEAD WIDE BELT SANDER
Year of Mfg. : 2000
Condition : Good Condition
Elect / Voltage : 380/440 V, 50/60 Cy, 3 Ph.
Special Note : Great Value

FOB / Region : EUROPE
Appr. Repl. Cost. : €0
Price : €18,500 *
Comment : Good condition machine, well equipped.
Leasing : Lease for € 376/Mo. at NCL

	Please ask me
	<p>Joe Retzlaff 800-374-5009 ext. 348 Intl. +1 704-841-2001 ext. 348 joe.retzlaff@exfactory.com</p>

* Pricing is valid at the time of printing and subject to change at any time.

Description :

- **SCM SANDYA CLK 3 G - 3-Head Wide Belt Sander 1,100 mm (43")** working width. Equipped with (2) Contact rollers and (1) Fine sanding platen head.

Head configuration:

- **1st Head:** Steel contact roller 160 mm (6,3"), spirally grooved, driven by 18,5 kW (25 HP) motor.
- **2nd Head:** Contact roller rubber, spirally grooved.
- **3rd Head:** Finishing platen with electronic sectional pad.
- Sanding Belt width 1,115 mm x length 2,150 mm (44" x 84.6").

Feed system: Variable feed speeds 4, 5 - 9 m/min (15 - 30 FPM), natural rubber feed belt. Automatic thickness adjustment. Automatic feed belt tracking and tensioning device, motorized rise and fall of working table. Part thickness 4 mm (0.2") to 170 mm (6.7"). Roller tables front & back of the machine.

Sales - Liquidations - Auctions - Appraisals - Consulting



Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries

Features:

- Electronic sanding belt tracking.
- Digital readout of part thickness and conveyor belt speed.
- Infeed safety bar for operator protection and over-sized parts.
- Front and rear emergency push button.
- Automatic star-delta starters of the main motors.
- Overload protection & load meters on main motors.
- Isolation class IP54.
- Automatic brakes for rapid shutdown of operating groups.

Automatic emergency stop for:

- sanding belt breaking
 - loss of sanding belt tension.
 - lateral outplacement of sanding belt
 - absence of compressed air
 - overload on main motors.
- Machine in compliance with **CE-regulations**

Actual model is: **SCM SANDYA CLK 3 G - 3-Head Wide Belt Sander 1,100 mm (43")**

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Tel: +1 704-841-2001 | Fax: +1 704-841-1200
Warehouse & Showroom: 8191 Logistic Drive, Ste. E | Zeeland, MI 49464 USA | Tel: +1 616-772-1520 | Fax: +1 616-772-1690