



Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries



Date : 04/26/2024 - 9:48 PM *
EXF # : SX-012870
Category : SANDERS-MULTI.HD/POLISHER
Brand / Model : D M C "UNISAND K"
Machine Type : WIDE BELT (50" - 90", 3-HEAD)
Year of Mfg. : 2007
Condition : Very good condition
Elect / Voltage : 460 V, 60 Cy, 3 Ph.
Special Note :

FOB / Region : SOUTH
Appr. Repl. Cost. : \$ 132,000
Price : **\$ 65,000 ***
Comment :
Leasing : Lease for \$ 1,306/Mo. at
NCL



Please ask me

Joe Retzlaff
800-374-5009 ext. 348
Intl. +1 704-841-2001 ext. 348
joe.retzlaff@exfactory.com

* Pricing is valid at the time of printing and subject to change at any time.

Description :

- **DMC UNISAND K 1350 M2 1,350 mm (53.15") 3-Head Veneer Sander**

For lacquer sanding, veneer cut, light calibration cut.

NOTE: The following specifications need to be confirmed by Seller.

Specifications:

- Working Thickness 4 - 200 mm (0.16" - 7.87").
- 1st Head: TA Cross belt sanding unit, with Electrically-controlled link sanding pad, 150 mm x 6.550 mm (5.91" x 257.87") Sanding belt, Variable sanding belt speeds 2 - 20 MPS (6.6 - 65.6 FPS), 15 kW (20 HP Motor),
- 2nd Head: "R-320" 320 mm Dia. (12.60") Shore 40 SH Spirally-grooved contact roller, Soft rubber version, 1,370 mm x 2,620 mm (53.94" x 103".15") Sanding belt, Variable sanding belt speeds 2 - 20 MPS (6.6 - 65.6 FPS), 15 kW (20 HP Motor).

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328



**Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries**

- 3rd Head: Superfinishing pad with "EPICS" Electronic sectional pad, (46) Sections, 1,370 mm x 2,620 mm (53.94" x 103.15") Sanding belt, Variable sanding belt speeds 2 - 19 MPS (6.6 - 62.3 FPS), 15 kW (20 HP Motor), Pneumatic belt tensioning, Intermittent belt-emitting device, Automatic infrared band control.

Equipped with:

- Oscillating belt cleaning blowers on all heads.
- Vacuum conveyor feed belt, with Variable feed speeds 3.5 to 18 MPM (11.5 - 59.1 FPM), 4 kW (5-1/2 HP) Drive motor, 15 HP Blower motor with Fan silencer.
- 200 mm (7.87") Dia. Panel cleaning brush with 1.5 kW (2) HP Motor.
- "HYDRA V-PAD" Touchscreen control.

Weight: 10,500 Lbs.

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328