

×

**Date:** 04/18/2024 - 8:27 PM \*

**EXF #:** AP-300009

Category: ABRASIVE PLANER & SANDERS

Brand / Model: EMC "FLEXY 1350 3WRR"

Machine Type: WIDE BELT SANDER (53" 3-HEAD)

Year of Mfg.: 2024

Condition: Brand New w/Warranty

Elect / Voltage: 220/440 V, 60 Cy, 3 Ph.

Special Note: Brand New

FOB / Region: MIDWEST

Appr. Repl. Cost.: \$ 135,000

Price: \$ 0 \*

Comment: High Tech Wide Belt

European Sander at a Great

Pri

**Leasing:** Call for Quote

\_\_\_\_\_\_\_



Please ask me

**Louis Sicotte** 

800-374-5009 ext. 329

Intl. +1 704-841-2001 ext. 329 louis.sicotte@exfactory.com

\* Pricing is valid at the time of printing and subject to change at any time.

#### **Description:**

• EMC FLEXY 1350 3WRR Finishing Sander with (3) Sanding Heads; Planer Head, Roller, Roller.

Useful working width 1,350 mm (53"). Working thickness min./max. 3 - 190 mm (1/8" - 7-1/2").

### **Head configuration:**

1st Head: Planer Head "W"

- Cutter head knives diameter 140 mm (5-1/2").
- Shaft for helicoidal position knives with (380) Interchangeable knifes with 4 cutting edges, 14 x 14 x 2 mm.
- Sectioned pressure bars in 24 independent segments.

Sales - Liquidations - Auctions - Appraisals - Consulting



- Anti kickback protection made of 70 independent elements.
- On-Off pneumatic cylinder for planer. group in working position.
- Working pressure adjustment.
- Motor power 22 kW (30 HP).
- Automatic Star-delta starter.
- Speed rotation: 35 m/Sec (115 FPS).

2nd Head: Steel Roller "R", Belts dimensions: 2,620 x 1,370 mm (103" x 54").

- Roller diameter: 250 mm (10"), spirally grooved.
- Electronic motorized roller pressure adjustment "Grit-set system".
- Constant control to any position with accuracy 0.02 mm.
- · Rotation: Against feed (clockwise).
- Motor power: 15 kW (20 HP) with Automatic star-delta starter.
- Abrasive Belt cutting speed: 18 m/Sec (59 FPS).
- Air Jet Blower for abrasive belt cleaning.

3rd Head: Roller "R", Belts dimensions: 2,620 x 1,370 mm (103" x 54").

- Roller diameter: 250 mm (10").
- · Roller rubber hardness 85 Shore.



- Constant control to any position with accuracy 0.02 mm.
- · Rotation: Against feed (clockwise).
- Motor power: 15 kW (20 HP) with Automatic star-delta starter.
- Abrasive Belt cutting speed: 18 m/Sec (59 FPS).
- Air Jet Blower for abrasive belt cleaning.

### Feed system:

#### Constant pass line, 900 mm (35.4") from floor

- Idle table rollers support in infeed and outfeed.
- Rubber covered presser rollers, grooved.
- Variable feed belt speed, adjustable from 3 to 18 m/Min (9.8 59 FPM) Inverter Controlled.
- Large diameter screws on machined guides with columns and pistons.
- Automatic feed belt centering device.

#### **General Machine Features:**

- Independent main motors.
- Analog ammeters, for each motor, on main control cabinet.
- Electronic motorized grit set system, control from touch screen for each (head) working group.

#### Electronic programmable color TOUCH SCREEN display, 7" wide

• PLC with micro-processor of latest generation, modular and expandable.



- Connection USB, RS232, Ethernet 10/100/1000.
- Memory capacity: 100 working programs or more.
- · Graphic synoptic to facilitate programming.

#### Software facilities:

- Automatic motor sequence starting.
- Command, programming and display for all electronic pad functions.
- · Command, programming and display for thickness.
- Command, programming and display for feeding.
- Command, programming and display for all inverters.
- Command, programming and display for selected groups.
- Command, programming and display for blowers, including compressed air saving function.
- Display report and reset of alarms (self diagnostic) with memory records.

#### **Options Included:**

Vacuum bed. 4 kw Vacuum unit for holddown of smaller parts, mounted inside of the machine base

<u>Centralized Control Cabinet:</u> IP 54 protection against dust & moisture. Analog ammeter on main control cabinet. Table (Conveyor Bed) lifting-lowering thickness system electrically controlled. AUTOMATIC Delta - Star starter on abrasive belt motors.

<u>Centralized independent pneumatic control cabinet:</u> IP 54 protection against dust & moisture. Pneumatic air filter with automatic water-drain system. Pneumatic adjustment for "Grit set system". Pneumatic plant working without lubrication. Compressed air pressure 6 bar (85 PSI)



Sales - Liquidations - Auctions - Appraisals - Consulting