

Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries



Date : 04/20/2024 - 12:16 AM *

EXF #: DC-300159

Category: DUST COLLECTOR UNDER 20HP

Brand / Model: BELFAB "NBM6-30 CHIP TRANSFER"

Machine Type: DUST COLLECTOR WITH CHIP

TRANSFER

Year of Mfg.: 2024

Condition : Brand New w/Warranty

Elect / Voltage: 208/230/460 V, 60 Cy, 3 Ph

Please ask me

Bernie Straple 800-374-5009 ext. 339

Intl. +1 704-841-2001 ext. 339

Bernie.Straple@exfactory.com

Special Note:

FOB / Region: EASTERN CDN

Appr. Repl. Cost.: \$0

Price: \$ 0 *

Comment: Continuously remove

chips/dust with Pneumatic

Tran

Leasing: Call for Quote

* Pricing is valid at the time of printing and subject to change at any time.

Description:

• BELFAB NBM6-30 CHIP & DUST TRANSFER DUST COLLECTOR

Patented Modular Technology and heavy-duty construction for exterior use. Heavy Duty construction designed for interior or exterior use.

Specifications:

- <u>Each "NBM" filter module is fitted with;</u> (1) service door & (1) explosion door per NFPA safety regulations, and integrated compact hopper.
- Rated Capacity: Rated @ 9,000 CFM @ 9.5" static pressure, 7,600 CFM @ 10.4 static pressure.
- **Equipped with:** Direct drive centrifugal fan assembly with 30 HP "Hummer" blower motor, anti-spark cast aluminum impeller, 20" inlet diameter

Unit Includes:

Sales - Liquidations - Auctions - Appraisals - Consulting



Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

- (6) "NBM" filter modules, each with (18) 7" x 60" Poly Twill cloth filter tubes; 990 sq. ft. total cloth area (165 sq. ft. per module) w/Continuous Dust Disposal Capacity.
- Pneumatic Chip / Dust Transfer System with (1) 7.5 HP and (1) 5 HP material handling blowers, continuously discharges chips and dust for re-cycling or disposal.
- (1) Electrical Control Panel w/ Shaker Mechanism to include; (4) Interlock Starters; (1) Soft start for the main blower, (2) for the Pneumatic Dust Transfer System and (1) for the shaker mechanism.

Security System for Air Return:

• (1) 20" Explosion Back Draft Damper, (1) 24" Fire Damper with status signal, (1) 24" Derivation Tee, (1) 24" Abort Damper and (1) Single Zone Spark Detector. *(Optional; pricing upon request)*

CALL FOR PRICING