

# Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries



**Date :** 03/29/2024 - 8:12 AM \*

**EXF #:** DM-300045

Category: DOOR ENTRY & STAIR EQUIP.

Brand / Model: DOTUL "MT-200"

Machine Type: RAISED PANEL ENTRY DOOR

SYSTEM

Year of Mfg.: 2024

Condition: Brand New w/Warranty

Elect / Voltage: 230/460 V, 60 Cy, 3 Ph.

Special Note: Great Value

FOB / Region: WEST COAST

Appr. Repl. Cost.: \$ 64,500

Price: \$ 0 \*

Comment: Not many such versatile high

quality 120" length m

Leasing: Call for Quote

\* Pricing is valid at the time of printing and subject to change at any time.

Please ask me

**Tony Cornacchione** 800-374-5009 ext. 432 Intl. +1 704-841-2001 ext. 432

TCorn@exfactory.com

### **Description:**

• **DOTUL** *MT-200* Raised Panel Door Machine machines **entry door** stile and rail door parts as well as **cabinet door** parts. One operator to machine profiles to the rail copes, stile and rail sticking and raised panels with rapid change over all on one machine.

#### **Features Include:**

- One operator to machine all profiles for stiles and rails on one machine, along with raising all panels both edges top and bottom.
- Machines door stiles up to 120" in length.
- Capacity for machining a 6" arc on panels and rails, and raises both face on a raised panel at the same time (arc size varies depending on cutter diameter).



# Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

- Raise a curved panel up to 6" radius both on rails and panels.
- Hydraulic pump unit for accurate table speed control.
- Simple guide system follows templates for curved or arched profiles and is quickly repositioned for straight machining profiles.
- Cutterhead knives can be stacked on the same spindle to eliminate changing machines to machine door parts.
- Easy stop system for door stiles or rail lengths.
- Heavy duty 15 HP motor, allows for high speed cutterhead to eliminate unnecessary sanding.
- Full length hold down bar, to ensure flat profiling or machining on parts.
- More than one part may be milled at one time.
- Easy positioning of parts on a precision ground, cast iron table ensures accurate stile rail and panel machining and alignments.

#### **Specifications:**

- Spindle Motor 15 HP @ 7,000 RPM; Hydraulic Motor 1 HP; Feed Speed 0-80 FPM.
- Spindle Diameter 40 mm; Spindle Height 8"; Depth of Radius Cut 6"; Min. Radius Cut 6" (based on cutter diameter) machine door stiles up to 96" in length.



### Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

 Dimension: Length 120"; Operating Length 228"; Width 48"; Height 48". Weight 4500 lbs. Air Supply Required 100 PSI

Note: Delivery time is about (12) weeks.