



Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries



Date : 04/26/2024 - 7:50 PM *
EXF # : EM-010002
Category : END MATCHERS
Brand / Model : CANTEK "CFS-100/EM-12"
Machine Type : DEFECTOR & END MATCHER/FINGER
JOINT BLOCK
Year of Mfg. : 2024
Condition : Brand New w/Warranty
Elect / Voltage : 230/460 V, 60 Cy, 3 Ph.
Special Note :

FOB / Region : PACIFIC NORTHWEST
Appr. Repl. Cost. : \$ 0
Price : \$ 0 *
Comment : Unique Defect Saw and End
Matcher System - High Pr
Leasing : Call for Quote



Please ask me

Louis Sicotte
800-374-5009 ext. 329
Intl. +1 704-841-2001 ext. 329
louis.sicotte@exfactory.com

* Pricing is valid at the time of printing and subject to change at any time.

Description :

- **CANTEK MODEL CFS100 / EM-12 DEFECT SAW AND END-MATCHING SYSTEM:**

Consisting of a CANTEK model "CFS-100" Optimizing Cut-Off Saw followed by a CANTEK Model "EM 12" Through-Feed End Matcher and with the following specifications and features:

CANTEK "CFS-100" OPTIMIZING CUT-OFF SAW

- Up to 20 mm X 200 mm or 100 mm X 100 mm(3/4" X 7.87" or 3.9" X 3.9" cutting capacity with 18" x 30 mm bore sawblade is driven by a 10 HP motor driving the saw spindle at 3,200 RPM; 2.7 HP servo drive feed system drives the stock up to 260 FPM; 0.787" min. distance between crayon marks; requires 75 to 80 PSI at the saw and 100 to 120 PSI at defect blow-off station. Machine comes completely wired and programmed.
- Machine is ideal for separating crayon marked waste zones from useable material before entering into a feed-thru End Matcher; provides (3) times greater production than manual cut-off saws.

5% + Material recovery (yield increase) over manual cutting; compact and user-friendly design; controller adopts an industrial grade computer that employs a 32-bit floating-point DSP system and features flash and

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328



**Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries**

battery backup SRAM for double security; superior to conventional PC-based controls, it can fully eliminate the machine going down or being damaged due to a poor environment, such as, unstable voltage, high temperature, sawdust, etc.

- With defect blow-off system combined with computerized logic control permits the blow-off time and the length of defect to be set as desired; provides efficient defect removal and eliminates defects from bumping against the sawblade, resulting in the machine going down or sawblade damage.
- Computer control provides easy and fast maintenance; feed system driven by a servo motor for fast and accurate motion and position control; max. feed speed up to 260 FPM; cutting rate up to 80 cuts per minute with cutting accuracy within approx. $\pm 1\text{mm} / 0.40''$; control employs a touch screen for easy learning and operation.

Features:

- New machine design features maximum maintenance convenience; high quality electric components provide maximum dependability; safety guards for maximum operator protection; 48" long infeed table standard - longer available option; 18" carbide blade included.

(5) Cutting modes include:

- Adjustable end cuts to a max. of 10mm (0.4")
- Fixed length of cutting mode.
- Sequential cutting mode with (10) sets of cutting sizes held in memory (for sequential cutting mode only).
- Cutting on fluorescent marks with double-end trimming (perfect solution for end matching).
- Reading fluorescent marks with double end trim, fixed-length, random length end match, and finger joint block cutting.

CANTEK "EM-12" END MATCHER

- Continuous through-feed system; handles random length min. 10.6" to any length x 0.4" to 1.38" thickness x 12" width capacity;
- 295 FPM max. feed speed; average speed of 75 FPM based on 6'-6" board lengths; with 118" infeed and 98" outfeed tables;

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328



**Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries**

- 5.5 HP Shaper motors, 1 HP feed motor and 1/2 HP cutter stroke motor and 24-volt control system; clamping from the top and outside side; 40 mm spindle dia.;
- 6" Dia. dust outlets; requires 85 PSI @ 12 CFM and a 12.5 total connected load at 230/460/575 Volt, 60 Cy, 3-Phase operation.

Standard features include:

- (1) Set tongue & groove cutterheads, heavy-duty self-supporting mainframe; compact design requires minimum floor space;
- Capable of processing material as short as 11" to an unlimited length;
- Variable speed through-feed system is controlled by frequency inverter; VFD mechanical drives for better control and elimination of surging as found with worn hydraulic drives.

The through-feed system allows the tongue to be cut simultaneously on the tail of one board and the leading edge of the next board; powered top urethane rolls and spring-loaded bed rollers feed the material into position for processing; pneumatic side pressure system ensures the material is held square against the fence; safety and noise reduction enclosure.

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328