



Machinery for the Woodworking, Stone,  
Glass, Plastic, and Metalworking Industries



**Date :** 04/19/2024 - 4:36 PM \*  
**EXF # :** MF-013001  
**Category :** MOULDERS - FEED THROUGH  
**Brand / Model :** CAM-WOOD "SM-236UX"  
**Machine Type :** MOULDER (FEED THROUGH)  
**Year of Mfg. :** 2024  
**Condition :** Brand New w/Warranty  
**Elect / Voltage :** 230 or 460 V, 60 Cy, 3 Ph  
**Special Note :**

**FOB / Region :** WEST COAST  
**Appr. Repl. Cost. :** \$ 80,900  
**Price :** **\$ 79,900 \***  
**Comment :** Need that universal spindle  
for saw or profile cut  
**Leasing :** Lease for \$ 1,596/Mo. at  
NCL



Please ask me

**Torry Hiddema**  
800-374-5009 ext. 371  
Intl. +1 704-841-2001 ext. 371  
torry.hiddema@exfactory.com

\* Pricing is valid at the time of printing and subject to change at any time.

#### Description :

- **CAM-WOOD Model SM-236U Moulder Feed Through**

6-Head (B-R-L-T-T-U), **working cap. 9" x 4-3/4"**

#### Specifications:

- **Head sequence:** Bottom 10 HP, Right 10 HP, Left 10 HP, Top 15 HP, Top 15 HP and Universal 7.5 HP motor.
- Max. (Min.) Working Thickness 4-3/4"
- Min. Working Length 9½"
- Feed Motor 7½ HP and Elevation motor 1½ HP

**Sales - Liquidations - Auctions - Appraisals - Consulting**

**EX-FACTORY INC.:** 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068  
**Warehouse & Showroom:** 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328



Machinery for the Woodworking, Stone,  
Glass, Plastic, and Metalworking Industries

---

- **Spindle Dia.:** 40 MM with cutterhead speed of 6,000. Mechanical digital readouts for all spindle adjustments, as well as chip breakers and pressure elements. Tool cutting circles: vertical spindles 5" to 6.25" and top spindles 5" to 7".
- **Variable Feed:** From 16 ~ 110 FPM with LED speed readout. Over-sized top and bottom rollers run synchronized, ensuring smooth feeding. The three independent section pneumatic pressures for the infeed rollers, in-process rollers, and outfeed rollers can be set with individual pressure allowing for consistent feeding.
- **Universal spindle** with 270° rotation from the left side.
- **Includes:** Infeed table 2M (6'6") with manual table lubrication ports. Side pressure roller at infeed; Hard chrome-plated table for maximum wear resistance. Full sound and safety enclosure and manuals.

---

**Sales - Liquidations - Auctions - Appraisals - Consulting**

**EX-FACTORY INC.:** 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068  
**Warehouse & Showroom:** 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328