

## Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries



**Date:** 04/20/2024 - 1:17 AM \*

**EXF #:** MF-300014

Category: MOULDERS - FEED THROUGH

Brand / Model: CAM-WOOD "SM-155AX"

**Machine Type:** MOULDER (FEED THROUGH)

Year of Mfg.: 2024

**Condition:** Brand New w/Warranty

Elect / Voltage: 230 V, 60 Cy, 3 Ph.

**Special Note:** 

FOB / Region: WEST COAST

Appr. Repl. Cost.: \$ 39,990

Price: \$ 39,800 \*

**Comment:** Great machine for the \$\$;

...Hard to find value!

**Leasing:** Lease for \$ 809/Mo. at NCL

Please ask me



800-374-5009 ext. 371

Intl. +1 704-841-2001 ext. 371 torry.hiddema@exfactory.com

\* Pricing is valid at the time of printing and subject to change at any time.

#### **Description:**

• CAM-WOOD SM-155AX Feed Through Moulder

5-Head Moulder with a 6" width and a 4.75" max. thickness capacity.

#### **Overall Description:**

- Cast Iron mainframe to maximize stability & minimize vibration during operation for years of use.
- Fully enclosed sound hood with lift-up door for easy set-up access.
- Adjustable infeed table w/fence for straightening rough sawn material.
- 16 66 FPM Variable feed speed system with top-driven rollers.
- All spindle adjustments except 1st bottom spindle with mechanical digital readouts.



## Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

• **Left and Top** spindles with mechanical Digi-set readouts. Chipbreaker and pressure element with mechanical digital readouts for accurate adjustment and precise settings.

**Complete with:** 5' Infeed table length, Chromed table plates, fences, and pressure shoes. Manual Waxilit pump, Central lubrication of the machine from the front side.

### **Specifications:**

- Max. (Min.) Working Width 6" (3/4")
- Max. (Min.) Working Thickness 4-3/4" (5/16")
- Min. Working Length 9½".
- 1st Spindle Horsepower 7½ HP.
- 2nd, 3rd Spindle Horsepower 5½ HP, 5½ HP;
- 4th, 5th Spindle Horsepower 10 HP, 71/2 HP.
- Cutterhead Dia.: 1st Bottom Head 5" dia.; 2nd, 3rd Vertical Head 5" 6-1/4" dia.: 4th, 5th Head 5" 7" diameter.
- Feed Motor 4 HP.
- · Elevation 1 HP motor.
- · Spindle Diameter 40 mm.



# Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

- Cutter Head Speeds 6,500 RPM.
- Variable Feed Speeds 16 ~ 66 FPM.
- Pneumatic Air 90 PSI (5 CFM by bolume)
- Dust Outlet Diameter 5" x 5"
- Net Weight 5,900 Lbs; Gross Weight 6,700 Lbs

### Includes:

Operator/spare parts manuals and setup tools.