

Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries



Date: 04/24/2024 - 8:11 AM *

EXF #: MF-300029

Category: MOULDERS - FEED THROUGH

Brand / Model: CAM-WOOD "SM-124TAX"

Machine Type: MOULDER (FEED THROUGH)

Year of Mfg.: 2024

Condition: Brand New w/Warranty

Elect / Voltage: 220/440 V, 60 Cy, 3 Ph.

Special Note:

FOB / Region: WEST COAST

Appr. Repl. Cost.: \$ 26,900

Price: \$ 26,500 *

Comment: One of the most compact

Moulders on the market!

Leasing: Lease for \$ 538/Mo. at NCL

Please ask me



Intl. +1 704-841-2001 ext. 371 torry.hiddema@exfactory.com

Description:

CAM-WOOD SM-124TAX Feed Through Moulder

4-Head Moulder with a 11-3/4" width x 9" maximum thickness when used as a 2-sided planer, and 10-1/4" width x 4" maximum thickness when used in 4-sided operation (please see literature).

Equipped with:

- Cast Iron mainframe to maximize stability & minimize vibration during operation for years of use.
- Fully enclosed sound hood with lift-up door for easy set-up access.
- Adjustable infeed table w/fence for straightening rough sawn material.
- 11 52 FPM Variable feed speed system with top-driven rollers.
- All spindle adjustments with mechanical digital readouts.

^{*} Pricing is valid at the time of printing and subject to change at any time.



Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

 Left and top spindles with mechanical digi-set readouts. Chipbreaker and pressure element with mechanical digital readouts for accurate adjustment and precise settings.

Complete with: 40" Infeed table length, Chromed table plates, fences, and pressure shoes. Manual waxilit pump, Central lubrication of the machine from the front side.

SPECIFICATIONS SM-124TA

Max. (Min.) Working Width 10-1/4"
Max. (Min.) Working Thickness 4"
1st Spindle Horsepower 4.1 HP - 7,000 RPM
2nd, 3rd Spindle Horsepower 4.1 HP - 7,000 RPM
4th, Spindle Horsepower 4.1 HP - 7,000 RPM
Feed Motor 1/2 HP
Spindle Diameter 40 MM
Cutter Speeds 6,500 (RPM)
Variable Feed Speeds (FPM) 17 ~ 66
Cutter head Diameter 1-1/4" or 30 mm
Pneumatic Air 90 PSI (CFM) 5
Dust Outlet Diameter 5" x 4"
N.W. 1,157 Lbs
G.W. 1,366 Lbs

Includes:

Operator/spare parts manuals and set-up tools.