

×

Date: 05/08/2024 - 3:28 PM *

EXF #: MF-300032

Category: MOULDERS - FEED THROUGH

Brand / Model: CAM-WOOD "SM-632HSX"

Machine Type: MOULDER (FEED THROUGH)

Year of Mfg.: 2024

Condition: Brand New w/Warranty

Elect / Voltage: 230 or 460 V, 60 Cy, 3 Ph

Special Note: Reduced

FOB / Region: WEST COAST

Appr. Repl. Cost.: \$ 185,000

Price: \$ 173,900 *

Comment: High Speed Moulder 12"

capacity - available as "Jo

Leasing: Lease for \$ 3,456/Mo. at

NCL

Please ask me



Intl. +1 704-841-2001 ext. 371

torry.hiddema@exfactory.com

* Pricing is valid at the time of printing and subject to change at any time.

Description:

- CAM-WOOD SM-632 HS 6-Heads High-Speed Trough Feed Moulder
 - (6) Heads (B-R-L-T-T-B), working cap. 12-1/2" x 6-1/4"".

Specifications:

- Max/Min working width 12 " 3/4"
- Max/Min thickness 6" 5/16"
- Minimum length 9-1/2"
- Head sequence: Bottom 15 HP, right 15 HP, left 15 HP, top 20 HP, top 20 HP and bottom 20 HP motor.



- All Horizontal spindles have outboard bearings
- Spindle dia. 50 mm with cutterhead speed of 6,200 RPM.
- All spindles are equipped with mechanical digital readouts, "Dual mechanical" readouts on the left and top spindles. Mechanical readouts for pressure elements and chipbreakers; all chipbreakers and pressure elements with pneumatics.
- Feed works: Inverter driven 15 HP feed system with feed speeds of 20 260 FPM.
- Infeed table 2M (6'6"), chromed tables, and fences. Side pressure roller mounted at infeed.

Features and complete with:

- Feed speeds ranging from 20' ~ 260' per minute are a standard feature.
- The full safety enclosure also works as a chip guard and helps to reduce noise.
- Table surface is hard chrome-plated for maximum wear resistance.
- All manually adjusted turning parts are housed in dry bearings for oil-free lubrication.
- One piece cast iron machine frame and table is especially normalization heat treated for maximum stability and rigidity.
- Fence adjustment is quickly accomplished by a quick-setting lever.



- The three independent section pneumatic pressure for the infeed rollers, in-process rollers and outfeed rollers can be set with individual pressure allowing for consistent feeding results and outstanding effect.
- All control levers for the spindles are located at the front of the machine for convenient adjustment.
- Each spindle is provided with a mechanical digital readout, giving accurate adjustment.
- Vertical spindle adjustment up to 80 mm, allows fitting several tools on the vertical spindle, eliminating troublesome cutter change.
- Separate adjustment of vertical spindle and insert table permits the table to be positioned extremely close to the cutterheads for added cutting stability.
- An individual motor drives each spindle and is separately mounted to eliminate spindle chattering during high-speed running.
- Centralized lubrication system

Available options:

- Automatic Jointer for all (6) heads add: ...\$45,600
- Digital (electronic) display for X and Y axis for each head add \$ 3,200 /per head
- NC Automatic positioning control system. This option consists of motorized adjustment of the head control from the main screen of the machine.

This option include:

15" HMI (1000 memory setting),



- Servo motor positioning, Simple and easy to operate.
- · Width and thickness quickly & auto set-up
- Tools management system
- Lateral chain feeder (quoted with customer material specifications)
- For 6 heads machine add \$82,800
- For 7 heads machine add \$ 90,600