

Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

×

Date: 04/26/2024 - 1:25 PM *

EXF #: ML-300193

Category: MATL. LIFT-SCISS. & HOIST

Brand / Model: ANVER "VT 250"

Machine Type: VACUUM LIFT

Year of Mfg.: 2024

Condition: Brand New w/Warranty

Elect / Voltage: 230 or 460 V, 60 Cy, 3 Ph

Special Note:

FOB / Region: NORTHEAST

Appr. Repl. Cost.: \$0

Price: \$ 0 *

Comment:

Leasing: Call for Quote

Please ask me



Bernie Straple 800-374-5009 ext. 339 Intl. +1 704-841-2001 ext. 339 Bernie.Straple@exfactory.com

* Pricing is valid at the time of printing and subject to change at any time.

Description:

ANVER VT 250 Vacuum Lift

Vacuum lifting for panels in horizontal orientation to reduce potential injury to employees. Suitable for diverse loads such as sheets of particle board, plywood, glass, steel and plastic.

- <u>Lifting capacity (using VB9HV-S Vacuum Station)</u>; 470 Lbs non-porous materials, 350 Lbs semi-porous and 235 Lbs porous load without reduction in performance.
- Automatically activated valve system to "lock on" to work piece.
- <u>User-friendly</u> Handle & Control Assembly for quick and precise control of the system and optimal ergonomics.
- Includes; Powerful 6.2 HP direct driven blower with 124 CFM air flow and 18" Hg suction.
- **Vacuum Lift Tube**, 7.9" dia., 8'-2" length, reinforced with 12-gauge wire and PVC material with 62" lift range and adjustable :hovering height" control.

Sales - Liquidations - Auctions - Appraisals - Consulting



Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

- Non-return safety valve to contain vacuum in case of power failure (load will descend).
- 360° Rotation on bearing-mounted top swivel.
- · Filter Assembly with gauge and adapters.
- Rigid operator vacuum gripper, Heavy duty beam assembly for VT, standard "H" configuration, 72" long w/ (2) 36" cross beams w/ manifold and quick release with (4) easy adjustable suction pads (6" x 12.5")
- Venting unit for easier release of air tight work piece.
- Suction hose 25' 6" length made of 2-3/8" Dia. wire-reinforced gray PVC material.
- Protective motor switch for 230V, 3-phase motor with 14.5 20 amp rating.