



Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries



Date : 07/05/2025 - 8:05 PM *
EXF # : PE-010131
Category : PALLET EQUIP./NAIL. MACH.
Brand / Model : BAKER "A"
Machine Type : BAND RESAW
Year of Mfg. : 2025
Condition : Brand New w/Warranty
Elect / Voltage : 220/440 V, 60 Cy, 3 Ph.
Special Note :

FOB / Region : MIDWEST
Appr. Repl. Cost. : \$ 0
Price : \$ 14,980 *
Comment : A great all-around resaw at a great price!
Leasing : Lease for \$ 304/Mo. at NCL

* Pricing is valid at the time of printing and subject to change at any time.

Description :

- **BAKER A Band Resaw**

1/4" to 6" (6 mm-152 mm) cutting height x unlimited lengths; accepts up to 7" x 7" max. incoming material with conveyor set at zero degrees.

Specifications:

- Fully variable feed speeds from 0 to 120 FPM and controlled by a hydraulic flow control valve; feed speeds relative to width of cut and hardness of material being cut.
- Band Wheels are dynamically balanced 28" dia. all steel wheels; Baker Low Profile Flat Guides with hardened tool steel guide plates.
- Blades are 13'-2" long x 1" or 1-1/4" wide x 0.035" hardback and blade tensioning is mechanical via spring.
- With 20 HP TEFC main drive; feedworks and conveyors run off hydraulic motor driven by main motor.



Please ask me

Bernie Straple
800-374-5009 ext. 339
Intl. +1 704-841-2001 ext. 339
Bernie.Straple@exfactory.com

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328



**Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries**

Standard features include:

- 20 HP Motor Standard; 6" wide hydraulically power driven conveyor with rough-top belting;
- 28" Diameter, dynamically-balanced, solid, all-steel band wheels;
- 13'-2" x 1" x 0.035" or 13'-2" x 1-1/4" x 0.035" hardback band blades; Baker's Exclusive Low-Profile Flat Plate Guide System with Rear Rollers;
- Hydraulic variable feed speed control, powered by main drive motor;
- Spring blade tensioning;
- Compact size (7' square) fits into almost any size of operation;
- Heavy-duty construction and simple to operate and maintain.
- **Dust Connection:** 4" diameter and 500 CFM required.

Available Optional equipment not included in price:

- Infeed and Outfeed Turnarounds;
- Simple Slide Return System; Rear non-powered hold-down;
- Diagonal cut attachment;
- Powered Hold-Over Wheels;
- Powered Hold-Down;
- 24 HP Gasoline engine

PRICING SUBJECT TO CONFIRMATION.

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328