

Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries



Date :	04/19/2024 - 10:36 PM *
EXF # :	RG-300013
Category :	RIP SAWS - MULTI-BLADE
Brand / Model :	CANTEK "MRS-300A"
Machine Type :	DIP CHAIN GANG RIP SAW
Year of Mfg. :	2024
Condition :	Brand New w/Warranty
Elect / Voltage :	460 V, 60 Cy, 3 Ph.
Special Note :	Great Value

Please ask me

Joe Retzlaff

800-374-5009 ext. 348 Intl. +1 704-841-2001 ext. 348 joe.retzlaff@exfactory.com

FOB / Region :	PACIFIC NORTHWEST
Appr. Repl. Cost. :	\$ 35,400
Price :	\$ 35,400 *
Comment :	This "new" CANTEK beats the price of many older US
Leasing :	Lease for \$ 720/Mo. at NCL

* Pricing is valid at the time of printing and subject to change at any time.

Description :

• CANTEK MRS 300 Multi Blade (Gang) Rip Saw:

General Description:

- Frame is Cast Iron, all the main parts are enclosed, ensuring protection and perfect stability.
- Straight line caterpillar style feeding with heavy guided chain. Chain blocks are special cast iron with heat treated & precision ground pins.
- Nickel chrome steel Saw Arbor with 70 mm OD dble. keyed quick removal sleeve.

Features & Includes:

- (3) Sets of Anti-Kickback Fingers (2) top, (1) bottom.
- Powered Rise & Fall to the pressure rollers.

Sales - Liquidations - Auctions - Appraisals - Consulting



- New style round Fence Bar support with quick shift long fence.
- Automatic Centralized lubrication system.
- Automatic Star-Delta Starter (slow speed start) and low voltage controls.
- C.E style European guard & safety features.
- Long fence for control of long material.
- Electrics to 230/460 or 575 Volts, 3-Phase, 60 Cycles.

Specifications:

- Max. Working Thickness, 4 5/8" (120 mm) with 15" Blade diameter.
- Min. Length, 20" standard or 12" with short stock attachment.
- Saw Sleeve Usable Length(between outside saws), 12" (305 mm).
- Sawblade Dia., 200 to 350 mm (8" to 14").
- Saw arbor Sleeve OD (Diameter), 70 mm; Saw arbor diameter, 50 mm.
- Saw arbor vertical adjustment, 3.6" (90 mm).

Equipped with:

- 50 HP Saw Motor Saw Arbor Speed 3,800 RPM.
- Powered Pressure Rollers (Rise/Fall), 1/2 HP motor.
- Feed Speeds 25 100 FPM (8 39 MPM); Feed Motor with 2 HP drive.

Sales - Liquidations - Auctions - Appraisals - Consulting



- (2) 6" Dia. Dust Hood.
- Table Size, 30" x 60"; Table Height from floor 33.5".

Other Information:

- Net Weight, 4,510 Lbs, Shipping Weight, 5,060 Lbs Machine Dimensions, 82.68" 59" x 56.5", Shipping dimensions, 71" x 67" x 63".
- Included: (1) Removable saw sleeve, (1) Set of (38) spacers; NOTE: Saw blades not included.

OPTIONAL EXTRAS - AVAILABLE:

Short Stock & Thin material cutting attachment

20mW Laser (FP MLC1320W) & Laser Holder w/6" Bolt on Base-Stand

(FP MBN03-XF8000).....\$ 1,020.00

OPTIONAL EXTRAS – AVAILABLE (Cont'd):

NEW – Single Blade Mechanical Quick Lock Collars that can be used on the 70mm sleeve for individual blade quick setting and locking process (no spacers required) – This is desirable especially if you have to quick change from size to size and you don't have the spacers to run a special size of product (Each CANMRS300-AM36-045-0)......\$ 210.00

75 KVA Auto Transformer for 230 Volt operation.

*230 volt machine can be ordered on request (factory order)

Electrics

Other Voltages for Stock machines are easily and inexpensively achieved through auto transformers that we normally have in stock. Please inquire.

Sales - Liquidations - Auctions - Appraisals - Consulting