

Machinery for the Woodworking, Stone, **Glass, Plastic, and Metalworking Industries**



Date :	04/24/2024 - 3:05 PM *
EXF # :	RG-300025
Category :	RIP SAWS - MULTI-BLADE
Brand / Model :	CAM-WOOD "TRS-3200X"
Machine Type :	SLAT RIPPER
Year of Mfg. :	2024
Condition :	Brand New w/Warranty
Elect / Voltage :	AS REQUIRED
Special Note :	

FOB / Region :	WEST COAST
Appr. Repl. Cost. :	\$ 27,990
Price :	\$ 25,750 *
Comment :	Perfect Saw for ripping narrow parts!
Leasing :	Lease for \$ 523/Mo. at I



Please ask me

Joe Retzlaff 800-374-5009 ext. 348 Intl. +1 704-841-2001 ext. 348 joe.retzlaff@exfactory.com

at NCL

* Pricing is valid at the time of printing and subject to change at any time.

Description:

CAM-WOOD TRS-3200 SLAT RIPPER - (1) Horizontal Bottom Saw or Moulder Spindle Bottom; •

The machine can rip extremely narrow parts. Ideal for shutters, louver slats, yardsticks, etc.

Features & Equipped with:

- Designed to meet the exacting standards required for high-quality production line use.
- CAM-WOOD's Slat Rip Saws are manufactured to precise tolerances and feature the newest designs for operator safety and volume production.
- All of these features combine to show what true value these machines are in today's highly competitive market.

Sales - Liquidations - Auctions - Appraisals - Consulting



- Precision fence assures absolute accuracy and is equipped with measuring gauge.
- Double anti-kickback fingers mounted at the infeed end of the machine provided maximum safety protection.
- Heavy-duty industrial TEFC motor ensures full-depth cutting capacity in all materials.
- Ruggedly constructed steel frame for durability and extended machine life.
- The variable speed feed works allow the machine to meet the cutting requirements of different materials.
- Saw head built to precise tolerances assures accuracy for all straight-line ripping operations and provides stellar cut quality.
- Top & bottom powered pneumatically tensioned feed rolls for precise feeding and cutting.
- Saw arbor is manufactured from alloy steel for dependability and anti-fatigue, heat-treated, precision ground, and balanced providing precise cutting performance.

Specifications:

- 12" Max. Cutting Width.
- 4-3/4" Max. Cutting Depth.
- 10" Min. Workpiece Length.
- 10" to 16" Dia. Sawblade Size.

Sales - Liquidations - Auctions - Appraisals - Consulting



- 4,000 RPM Spindle Speed.
- 12" Spindle Length
- 70 mm Arbor Diameter (with 2-keyways).
- 30 HP Rip Saw Motor
- 3 HP Feed Motor.
- 12 to 60 FPM Feed Speed (Variable).
- 1 HP Feed Roll Elevating Motor.
- 1/2 HP Saw Arbor Elevating Motor.
 - Footprint: 81" long x 40" wide x 60" high.

Sales - Liquidations - Auctions - Appraisals - Consulting