



Date : 07/02/2025 - 11:58 PM *

EXF #: RG-300032

Category: RIP SAWS - MULTI-BLADE

Brand / Model: CAM-WOOD "TRS-340-2MX"

Machine Type: MULTI-BLADE RIP SAW, (SHIFTING

BLADES)

Year of Mfg.: 2025

Condition: Brand New w/Warranty

Elect / Voltage: 230/460/575 V, 60 Cy, 3 Ph

Special Note: Best Buy

FOB / Region: WEST COAST

Appr. Repl. Cost.: \$ 120,000

Price: \$ 110,990 *

Comment: Amazing, Feature Loaded

Ripsaw for less than \$125,

Leasing: Lease for \$ 2,218/Mo. at

NCL

Please ask me



800-374-5009 ext. 348 Intl. +1 704-841-2001 ext. 348 joe.retzlaff@exfactory.com

* Pricing is valid at the time of printing and subject to change at any time.

Description:

CAM-WOOD TRS-340 M2 Gang Rip Saw With (2) Moveable Blades:

Capacity:

- Depth of cut with 14" dia. blades: 4" at movable blades, 4.3" at fixed blades
- Depth of cut with 12" dia. blades: 2.95" at movable blades, 3.34" at fixed blades
- Depth of cut with short stock holddown and 14" dia. blades: 3.14"
- Depth of cut with short stock holddown and 12" dia. blades: 2.36"



- Max. rip width cap. 13.4"
- Max material width, 25.6"
- Min. rip length, 22"
- Min rip length with short stock holddown, 15.8"

Other Specifications:

- Max. sawblade dia., 14"
- Min. sawblade dia., 12"
- Sawblade bore, 90 mm (3.54")
- Saw arbor dia., 70 mm (2.75")
- Arbor motor, 50 HP
- Arbor speed, 3,800 RPM with 50 or 60 HP motors
- Feed speed from 20 to 135 FPM
- · Feed motor by 3 HP VFD



- Overhead pressure roll raise & lower motor, 1/2 HP
- Dust collection; (2) 8" diameter
- Overall dims., 62" wide x 88" long x 72" high x 5,000 Lbs

Features:

- Machine combines edging, selective, and gang rip functions
- Control Panel can be located for easy access
- Edges of random width boards can be trimmed in a single pass
- The positions of the movable saw blades are accurately controlled from the control panel for fast and convenient sets.
- Saw blade movement is driven through precision ball screws along a linear slideway for accurate, effortless traverse
- Exclusive laser projection system ensures accuracy
- Digital display for saw blade traverse; readouts in inch and metric displays are switchable
- Pressure rolls are supported on both sides and hold stock firmly and evenly
- Overhead pressure roll mechanism includes powered raise and lower



- · Variable feed speed permits effortless ripping of a variety of stock; hard or soft, thick, or thin
- Double top and single bottom anti-kickback fingers, plus a side guard, provide excellent safety for the operator.
- Stepping motors drive precision ball screws for fast and accurate width settings.
- Same as above. f equipped with optional shifting fence and includes a digital display to accurately indicate fence travel
- Suspension of pressure plate from two sides helps prevent split or broken parts from damaging the saw arbor or saw blades
- Saw blade's movements are concentric for perfect rip accuracy and parallelism of ripped boards.

Comes standard with:

- (3) 15 Mw Laser
- · (2) Fixed saw seats
- (3) 12" Carbide Tipped Sawblades

Optional:

- TRS-FTAO-3: Automated In-Feed Table, 3 Meter Powered Conveyor System with Movable Fence, Shifting Laser Lights for 2-Moveable Blades for Rip Width Settings, and Digital Display,
- TRS-FTMU-3: 3 Meter Powered In-feed Table, Manual,



Sales - Liquidations - Auctions - Appraisals - Consulting