

×

Machinery for the Woodworking, Stone, Glass, Plastic, and Metalworking Industries

| Date : | 04/26/2024 - 1:35 PM * |
|-------------------|-----------------------------------|
| EXF # : | SW-300206 |
| Category : | SANDERS-1-HD., WB/DRUM |
| Brand / Model : | SUPERMAX TOOLS "SUPERBRUSH 13" |
| Machine Type : | BRUSH SANDER |
| Year of Mfg. : | 2024 |
| Condition : | Brand New w/Warranty |
| Elect / Voltage : | 110 V, 60 Cy, 1 Ph. |
| Special Note : | |

| FOB / Region : | MIDWEST |
|---------------------|--|
| Appr. Repl. Cost. : | \$ 4,630 |
| Price : | \$ 4,499 * |
| Comment : | A true workhorse! Best bang for your Buck! |
| Leasing : | Call for Quote |



Please ask me

Ed Webb 800-374-5009 ext. 377 Intl. +1 704-841-2001 ext. 377 Ed.Webb@exfactory.com

* Pricing is valid at the time of printing and subject to change at any time.

Description :

- SUPERBRUSH 13" Combination Brush/Drum Sander:
- SUPERBRUSH applications include, but are not limited to: White wood sanding, de-nibbing, sealer, and primer sanding applications, as well as UV roughing and reclamation projects. De-burring, graining, and polishing of steel, stainless steel polishing and aluminum finishing and solid surface materials. These sanders are well suited to shutter sanding, de-glossing and de-stressing. It can also be equipped with an optional sanding drum for surface sanding.
- **13" Sanding width**, 9" min. part length and 4" max. thickness (varies with drum/brush style), or as thin as 1/32", 6" to 8" Typical Brush diameter; driven by a 1-3/4 HP motor, 3/32" per turn height adjustment, depth gauge included. Dimensions: 35"D x 42"W x 44"H.
- Rubberized conveyor belt grips and pulls parts through the sander. via 0 -10 FPM variable speed feed system. 1-1/2" Dia., rubber covered, infeed and outfeed rollers provide tension to support the belt over reinforced steel conveyor bed. Bristle contact gauge (depth gauge) included.

Sales - Liquidations - Auctions - Appraisals - Consulting



- **RPM Gauge** displays brush speed, variable 400 1,200 RPM.
- Dust Hood: (1) 4″ Port, Hinged At Back, 600 CFM min. recommended.
- **Machine Design:** Cast stand, zinc-plated steel bed, centerless ground column tubes. Ball bearings are sealed and permanently lubricated.
- Machine comes with one (1) drum or brush of choice based on application.

Accessories: Casters, Infeed-Outfeed tables & DRO (Digital Depth Guage).

Shipping Dimensions: (L x W x H): 34-½″ x 45-½″ x 46-½″. Shipping Weight: 300 Lbs (approx.).

Sales - Liquidations - Auctions - Appraisals - Consulting