



Date : 04/26/2024 - 2:22 AM *

EXF #: SX-300051

Category: SANDERS-MULTI.HD/POLISHER

Brand / Model: EMC "UNDERTOP 1300 2+2"

Machine Type: WIDE BELT (SANDING LINE)

Year of Mfg.: 2024

Condition: Brand New w/Warranty

Elect / Voltage: 220/440 V, 60 Cy, 3 Ph.

Special Note: Brand New

FOB / Region: MIDWEST

Appr. Repl. Cost.: \$ 153,000

Price: \$ 0 *

Comment: Heavy Duty Wide Belt

Sanding Line, Top + Bottom

fr

Leasing: Call for Quote

* Pricing is valid at the time of printing and subject to change at any time.

Please ask me

Joe Retzlaff

800-374-5009 ext. 348 Intl. +1 704-841-2001 ext. 348 joe.retzlaff@exfactory.com

Description:

• EMC UNDERTOP 1300 2+2 - Wide Belt Sanding Line Top + Bottom, both with (2) Sanding Heads; Roller, Combination Head Roller/Pad.

Useful working width 1,300 mm (51"). Working thickness min./max. 3 - 160 mm (1/8" - 6-5/16").

Both Bottom + Top units are equipped as follows:

1st Head: Steel Roller "R", Belts dimensions: 1,900 x 1,320 mm (74" x 52").

- Roller diameter:190 mm (7-1/2"), spirally grooved.
- Constant control to any position with accuracy 0.02 mm.
- "Grit-set system".
- Rotation: Against feed (clockwise).



- Motor power: 22 kW (30 HP) with Automatic star-delta starter.
- Abrasive Belt cutting speed: 21 m/Sec (69 FPS).
- · Air Jet Blower for abrasive belt cleaning.

2nd Head: COMBINATION Unit "K", Roller/Pad. Belt dimensions: 1,900 x 1,320 mm (74" x 52").

- Roller diameter: 142 mm (5-5/8").
- Roller rubber hardness 45 Shore.
- Constant control to any position with accuracy 0.02 mm.
- "Grit-set system".
- Pneumatic controlled PAD with ON-OFF switch on main control panel.
- Rotation: Against feed (clockwise).
- Motor power: 15 kW (20 HP) with Automatic star-delta starter. Abrasive Belt cutting speed:18 m/Sec (59 FPS).
- · Air Jet Blower for abrasive belt cleaning.

Feed system:

- Constant pass line, 980 mm (38-9/16") from floor
- Idle table rollers support in infeed and outfeed.
- Rubber covered presser rollers, grooved.
- Variable feed belt speed, adjustable from 3 to 19 m/Min (9.8 62 FPM), Inverter Controlled, synchronized.



- Motorized height adjustment on 4 precision screws.
- Large diameter screws on machined guides with columns and pistons.
- Automatic feed belt centering device.
- Pre-welded machined working table.
- Pneumatic air floating pressure holddown shoes at infeed, in middle position, and in outfeed position.

General Machine Features:

- Independent main motors.
- Analog ammeters, for each motor, on main control cabinet.
- Electronic motorized grit set system, control from touch screen for each (head) working group.

Electronic programmable color TOUCH SCREEN LCD display, 7" wide

- Resolution 640 x 480 pixels.
- PLC with micro-processor of latest generation, modular and expandable.
- Memory capacity: 100 working programs or more.
- Graphic synoptic to facilitate programming. Front protection IP 65 against dust & moisture.

Software facilities:

- Automatic motor sequence starting.
- Command, programming and display for all electronic pad functions.



- Command, programming and display for thickness.
- · Command, programming and display for feeding.
- Command, programming and display for all speed control inverters.
- Command, programming and display for selected groups.
- Command, programming and display for blowers, including compressed air saving function.
- Display report and reset of alarms (self diagnostic) with memory records.

Options Included:

- Vacuum beds both on top + bottom, 4 kw (5,5 HP) each. Vacuum unit for holddown of smaller parts, mounted inside of the machine base with silencer.
- Telemetry for online support from EMC.

<u>Centralized Control Cabinet:</u> IP 54 protection against dust & moisture. Analog ammeter on main control cabinet. Table (Conveyor Bed) lifting-lowering thickness system electrically controlled. AUTOMATIC Delta - Star starter on abrasive belt motors.

<u>Centralized independent pneumatic control cabinet:</u> IP 54 protection against dust & moisture. Pneumatic air filter with automatic water-drain system. Pneumatic adjustment for "Grit set system". Pneumatic plant working without lubrication. Compressed air pressure 6 bar (85 PSI)

For a SCOTCH BRITE Brush roller, please add... US \$ 4,250 per side, bottom + top = US \$ 8,500