

Machinery for the Woodworking, Stone, **Glass, Plastic, and Metalworking Industries**



Date :	07/01/2025 - 9:01 PM *
EXF # :	SX-300085
Category :	SANDERS-MULTI.HD/POLISHER
Brand / Model :	CAM-WOOD "WS-DA3760X"
Machine Type :	WIDE BELT (12" - 39", 2-HEAD)
Year of Mfg. :	2025
Condition :	Brand New w/Warranty
Elect / Voltage :	220 V, 60 Cy, 3 Ph.
Special Note :	

FOB / Region :	WEST COAST
Appr. Repl. Cost. :	\$ 26,400
Price :	\$ 24,990 *
Comment :	Very well priced especially with all these feature
Leasing :	Lease for \$ 508/Mo. at NCL



Please ask me

Joe Retzlaff 800-374-5009 ext. 348 Intl. +1 704-841-2001 ext. 348 joe.retzlaff@exfactory.com

Lease for \$ 508/Mo. at NCL Leasing :

* Pricing is valid at the time of printing and subject to change at any time.

Description:

CAM-WOOD WS-DA3760 Wide Belt Sander, (2) Heads

With the two-head wide belt sander, you can accurately, and heavily sand your stock with the first drum head, and with the second combination head, you can give an unlimited fine finish.

Application:

- Rugged heavy-duty sheet metal construction designed for durability usage. •
- Powerful industrial motors drive sanding and auto infeed smoothly.
- Infeed and outfeed have spring-loaded hold-down rollers to ensure positive feeding without sanding marks.
- Combination platen & drum sanding head for best sanding choice such as:
- With the platen up, the sander functions as a drum-only machine, for sanding with a 40 ~ 100 grit belt.

Sales - Liquidations - Auctions - Appraisals - Consulting



- With the platen and drum same level, intermediate and final finishing is possible, using a grit of 120 ~ 180.
- With the platen down (below the drum), used for the fine finishing or lacquer sealer sanding, with 180 ~ 600 grit.

Head Configuration:

1st Head : 20 HP Drum

2nd Head : 15 HP Combination Head

Specifications:

- Max. Working Width 37" Max.
- Working Thickness 5".
- Min Working Length 12¹/₂".
- Sanding Belt Dimensions (W x L) 37" x 60".
- Dust Collection Hood (Dia x Holes) 6" x 2.
- Main Motors 20 and 15 HP.
- Conveyor bed Feed Motor 2 HP.
- Table Raising / Lowering Motor 1/2 HP
- Variable Feed Speed 20 80 FPM.
- Working Air Pressure 6 CFM.
- Exhaust Volume Require 2,400 CFM.
- N.W. weight 5,100 Lbs.

Sales - Liquidations - Auctions - Appraisals - Consulting



Equipped with and Features:

- Sanding platen with a quick release and lock down design for easy removal or loading of graphite platen.
- Computerized thickness adjustment control with accurate digital readout; key in the size desired and automatic table movement for sanding thickness within 0.005" accuracy
- Large size diameter contact drum is dynamically balanced, rubber-covered spiral grooves designed to provide considerable advantages for the effective removal of material.
- Special rubber feed belt for safe non-slipping, transporting the workpieces.
- The abrasive belts are tracked by oscillating cylinders linked to the upper roller. The edge of the belt is detected by an electric eye sensor, which in turn controls the air supply to the position via solenoid value. Also, one limit switch is located on each end of the top roller of the sandpaper for quick stop in case of belt breakage.
- The main table is designed with the convenient leveling adjustment which ensures greater stability with
 excellent tolerance providing a variable from 0" ~ 5" range sanding thickness.
- (4) Heavy-duty jackscrews power conveyor table elevation.

Sales - Liquidations - Auctions - Appraisals - Consulting