



Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries



Date : 07/06/2025 - 6:10 PM *
EXF # : VG-300001
Category : V-GROOVER/MULTI-BLADE SAW
Brand / Model : ZAFFARONI "MLS 130 P"
Machine Type : MULTI-BLADE PANEL SAW:
Year of Mfg. : 2025
Condition : Brand New w/Warranty
Elect / Voltage :
Special Note :

FOB / Region : MIDWEST
Appr. Repl. Cost. : \$ 105,000
Price : **\$ 95,000 ***
Comment : Zaffaroni world renowned
manufacturer of Multi Rip
Leasing : Lease for \$ 1,898/Mo. at
NCL



Please ask me

Bob Bullin
800-374-5009 ext. 346
Intl. +1 704-841-2001 ext. 346
bob.bullin@exfactory.com

* Pricing is valid at the time of printing and subject to change at any time.

Description :

- **ZAFFARONI *MLS 130 P PD* MULTI-BLADE PANEL SAW:**
- **Specifications**
Zaffaroni is the Top of the Line in Precision Multi Rip saws for Panels. Blade Depth is mechanically adjustable with a tolerance of ± 0.01 mm (0.0004"). The saw is so precise it can also be used for "V" grooving.

The Saw blades project through the table from below. A double row of hold down wheels are mounted above the saw, with 24 adjustable rollers to prevent contact with the blade.

Technical Characteristics:

- Working Width 1300 mm (51-1/8")
- Min. Panel Length 300 mm (11-7/8").

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328



**Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries**

- Motorized thickness adjustment from 0 - 70 mm (2-3/4").
- Adjustable projection of the saw blades from the working from 42 - 62 mm (1- 5/8" - 2-7/16") with circular saw blades or hogger trimmer up to 280 mm diam. (11").
- Working Table Height 1120 mm (44").
- Transport Speed from 3 - 45 MPM (9.8 - 147.6 FPM).
- Main Motor Power 37 KW (50 HP) with Belt Drive.
- Saw Blade Spindle 80 mm x 1310 mm (3-1/8: x 51-1/2"), with double tangs and automatic anti-rotation locking clutch.
- Spindle Speed 4,000 RPM.

Machine Features:

- Opening of the roller group through pneumatic cylinder with timer interlock for safety.
- Safety protection hood with sound absorbing materials to conform to ISO 7960/95 Norm.
- PLC logic control with digital communications through bus cable.

Spacer Sets: Machines require Spacer Sets and Saw Blades (not included) and pricing is available on request.

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328