



Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries



Date : 07/03/2025 - 11:30 PM *
EXF # : WH-300045
Category : WOOD WASTE GRINDERS
Brand / Model : WEIMA "TIGER 600"
Machine Type : LOW NOISE WASTE GRINDER
(HORIZONTAL FEED)
Year of Mfg. : 2025
Condition : Brand New w/Warranty
Elect / Voltage : 480 V, 60 Cy, 3 Ph.
Special Note :

FOB / Region : SOUTHEAST
Appr. Repl. Cost. : \$ 76,830
Price : **\$ 76,830 ***
Comment : Tiger 600 Horizontal Grinder
w/Conveyor;...a perfe
Leasing : Lease for \$ 1,535/Mo. at
NCL

* Pricing is valid at the time of printing and subject to change at any time.

Description :

- **WEIMA TIGER 600 Horizontal Slow Speed Grinder w/Vibratory Conveyor**

Specifications:

- 6" High x 23.6" wide max. infeed opening, 50-60 HP rotor motor, 14" dia. rotor grinds at 620 RPM (fixed rotor speed depending on application).
- Equipped with:
- **Patented "V-ROTOR"** design utilizes a v-groove rotor closely matched to grooves in the counter-knife to ensure uniform discharge free of splinters, reduce friction, and dedicate more horsepower to grinding.
- Features:



Please ask me

Jim Reedy
800-374-5009 ext. 455
Intl. +1 704-841-2001 ext. 455
jim.reedy@exfactory.com

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328



**Machinery for the Woodworking, Stone,
Glass, Plastic, and Metalworking Industries**

- (32) Replaceable back bolt-on cutter knives (welded knife holders standard, bolt-ons per customer request), recessed concave cutters with low clearance over the rotor extend cutter life, protect the bolts, and reduce machine wear.
- Infeed roller with replaceable wear strips for ease of maintenance, feed speed is controlled by monitoring the amp draw of the rotor, preventing "braking" or excessive pressure on the rotor, the vibratory infeed conveyor (12') is tied into the feed roll to eliminate binding.
- **9.85" (250 mm) Dia. dust collection outlet** (3,000 CFM required).
- **Includes:**
- Heavy Duty low-profile frame (15-3/4" passline height); integrated "plug-and-play" electrical control system with UL approved components (system UL certification available upon request for additional charge); up to 16' vibratory infeed conveyor available.

Sales - Liquidations - Auctions - Appraisals - Consulting

EX-FACTORY INC.: 1805 Sardis Road North | Charlotte, NC 28270 USA | Ph +1 704.841.2001 | Fax 704.644.8068
Warehouse & Showroom: 8191 Logistic Drive, Suite E | Zeeland, MI USA | Ph +1 616.772.1520 | Fax 704.644.8328